

# Portable Daylight Viewing Monitor



Includes carrying case with arm strap, shoulder strap, and hood.



		<b>TLM-0251<i>i</i></b>
LCD Panel	Type	TFT LCD
	Screen Size	2.45 Inch (Diagonal)
	Viewable Size	49.2mm (H) x 38.142mm (V)
	Dot Pitch	0.1025(W) x 0.163(H)
	View Angle (H/V)	90°/10°(T), 30°(B)
	Contrast Ratio	150:1
	Brightness	350cd/m <sup>2</sup> (Typical)
	Resolution	480 x 234
	Display Colors	NA
Control	Key Define	Brightness, Color
Power Supply	Input-Voltage	9VDC or battery (6 "AA")
	Consumption	2W
Video		Composite video, connector: 1 BNC
	Input	Level: 1.0Vp-p / 75Ω
	Output	1 BNC connector for CVBS loop-through output
	Adjustment	Video Control: Brightness, Color
	System Compatibility	NTSC : 15750Hz ± 500Hz / 60Hz
Accessory		Carrying Case
Additional Benefit		Daylight Viewable

- Compact, lightweight and portable design
- Monitor can be hand held or fastened to your arm with carrying case
- Operates on 6 AA batteries or AC power adapter
- BNC video input and loop-thru BNC output
- One time camera adjustment
- Daylight viewing for outdoor application