



Custom Assembly Checklist

- 1.) Connector part numbers: (if single ended-please advise if you would like the lead end blunt cut or prepped) Additional legs are possible.

End 1 _____
End 2 _____

- 2.) Equipment brand and model numbers:

End 1 _____
End 2 _____

- 3.) Pin out required. Please attach in separate document.

- 4.) Length required: _____ (please include unit of measure)

- 5.) RoHS compliance: Yes No

- 6.) Equivalent components acceptable: Yes No

- 7.) Application Type: Stationary In motion

Estimated cycles _____

- 8.) Environmental considerations:

Water Oil

Temperature Other _____



Custom Assembly Checklist

9.) Overmolding: Yes

Connector Breakout

End 1 _____

End 2 _____

No

10.) Power supply required: Yes

Version: North American International

Style: Wall mount Desktop

Voltage and current required _____

No

11.) Desired dock date: _____

12.) Requested quantities: _____
(ie 1...5...10...50...1000...?)

13.) Target price: _____

* Tolerances will be according to IPC/WHMA-A-620 unless otherwise specified-see below

Cable length	Tolerance		Cable length	Tolerance
≤ 0.3 m	+25mm -0		≤ 1 ft	+ 1 in - 0 in
> 0.3m-1.5m	+50mm -0		> 1 ft - 5 ft	+ 2 in - 0 in
> 1.5m-3.0m	+100mm -0		> 5 ft - 10 ft	+ 4 in - 0 in
>3.0 m	+150mm -0		> 10 ft	+ 6 in - 0 in