

It's so easy

uEye® 1220-M/C



0,36

Megapixels



USB2.0 CMOS WVGA Camera

Monochrome or Colour with Global Shutter

Your Eye in Machine Vision








www.net-usa-inc.com

- 752 x 480 pixels (WVGA)
- High quality CMOS sensors with square pixels, Global Shutter
- Up to 87 frames/s in full frame mode, over 100 frames/s using Area of Interest (AOI)
- Digital output
- uEye SDK (compatible to the FALCON SDK) and demo programs in scope of supply
- C-Mount
- Ultra small size and less weight: 34 x 32 x 27,4 mm (HxWxD), 62g
- Camera control via USB 2.0
- Mini-B USB AND screwable Micro D-SUB connector for industrial use
- Driver and Interfaces: Windows and Linux SDK, Twain, Direct Show (WDM), ActiveX, ActivVisionTools, Common Vision Blox, HALCON and NeuroCheck
- OEM modules available



USB2.0 camera



CAMERA SPECIFICATIONS	
	UI-1220-M/C
Resolution (pixels)	752x480
M - Model (b/w)	Yes
C - Model (colour)	Bayer RGB Pattern
Chip type / Chip size	1/3 Inch/5,4 mm
Cellsize (HxV) in μm	6 x 6
Shutter	Global
Scanning System	Progressive Scan
Sensor dynamics	60 dB
Frames per second	87
Binning	hor. & vert.
Subsampling	--
AOI	hor. & vert.
Mirror /Flip	hor. & vert.
Pixel Clock Frequency (Min/Max)	5/40 MHz
Shutter speed	60 μs - 1600ms
Hardware Gain	0-6dB
Hardware Trigger	async
Lens mount	C-Mount
IR filter	yes, removable
Interface	USB 2.0
Power supply	< 1 Watts
Operating temperature	0° - 50° Celsius
Regulations	CE, FCC Class B
Size (HxWxD) in mm	34 x 32 x 27,4
Weight	62 g



uEye Micro D-SUB connector Description

Pin	Assignment
1	Digital output -
2	Trigger input +
3	Shield
4	USB +5V
5	USB GND
6	Digital output +
7	Trigger input -
8	USB D+
9	USB D-

The uEye CMOS cameras are ultra compact cameras with USB 2.0 interface for industrial use. They are equipped with high quality sensors, industrial Design, C-Mount, a standard USB and additionally a screwable USB interfaces which offers also the trigger and digital output. Ready for professional use.

With it's USB 2.0 architecture, the cameras are ideally suited for use with PC, Notebook and Embedded Systems in image processing and factory automation.

The powerful -free of charge- uEye SDK and the yet available drivers and Interfaces for popular machine vision software allow e asy integration in applications. It's so easy!

AVAILABLE DRIVER AND INTERFACES

Windows 2000 und XP: uEye SDK, TWAIN, ActiveX, Direct Show (WDM), ActivVisionTools, Common Vision Blox, HALCON, NeuroCheck. Linux: uEye SDK

ACCESSORIES:

- USB cable
- Lenses
- USB2.0 Interfaces
- Software

